

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

# LISTING SERVICE

**LISTING No:** 3555-0855:100

Page 1 of 1

**CATEGORY:** Door with Integral Exit Hardware (Fire-Rated)

**LISTEE:** Openings, 40 W. Howard, Pontiac MI 48058  
Contact: Leon Yulkowski (810) 335-7380

**DESIGN:** Mineral-core steel-faced. Doors equipped with 16 ga. mild steel frame and continuous full-height hinge and "U" shaped full-height leading edge assembly operated by an integral panic bar. Refer to listee's data sheet for detailed product description and operational considerations.

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

**MARKING:** Listee's name, rating and Warnock Hersey label.

**APPROVAL:** Listed as a 1 -hour fire-rated door. Maximum sizes listed below:

Single	51" x 9'
Pair	102" x 9'
Double Egress	102" x 9'

06-03-93



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: **JUNE 19, 2002**

*Listing Expires **June 30, 2003***

Authorized By: **DIANE K. AREND**, Senior Deputy  
Program Manager